

BAC ISOTERMICO

TABLA DE GAMA

Modelo	Dimensiones exteriores			Dimensiones interiores			Peso	Volumen	Coef.K
	Anchura	Profundidad	Altura	Anchura	Profundidad	Altura			
BAC 50	610 mm	410 mm	485 mm	480 mm	280 mm	330 mm	17 Kg	44 litros	0,46 W/M2x°C
BAC 55	600 mm	500 mm	580 mm	415 mm	315 mm	410 mm	16 Kg	53 litros	0,38 W/M2x°C
BAC 75	800 mm	600 mm	438 mm	652 mm	452 mm	260 mm	18 Kg	77 litros	0,38 W/M2x°C
BAC 120	765 mm	600 mm	614 mm	610 mm	445 mm	430 mm	30 Kg	117 litros	0,30 W/M2x°C
BAC 150	800 mm	640 mm	660 mm	625 mm	470 mm	480 mm	32 Kg	141 litros	0,30 W/M2x°C
BAC 160	800 mm	600 mm	1050 mm	580 mm	370 mm	700 mm	50 Kg	150 litros	0,30 W/M2x°C
BAC 250	980 mm	900 mm	650 mm	800 mm	720 mm	455 mm	58 Kg	262 litros	0,35 W/M2x°C
BAC 260	996 mm	926 mm	810 mm	800 mm	720 mm	455 mm	73 Kg	262 litros	0,35 W/M2x°C
BAC 420	1200 mm	800 mm	1050 mm	1000 mm	600 mm	700 mm	90 Kg	420 litros	0,31 W/M2x°C
BAC 480	1200 mm	1000 mm	970 mm	1000 mm	800 mm	600 mm	112 Kg	480 litros	0,27 W/M2x°C
BAC 600	1200 mm	1200 mm	970 mm	1000 mm	1000 mm	600 mm	122 Kg	600 litros	0,25 W/M2x°C

Tel : + 33 (0)4 77 906 863

Fax : + 33 (0)4 77 903 495

www.olivo.fr



LEADER IN INSULATED CONTAINERS